

## FONDO E CARTELLA

### Fondo bombato e cartella inox a saldare

#### Fondo bombato inox



**Esecuzione:** inox 304 con estremità lisce - spessore 2 mm - finitura delle superfici burattate.

**A richiesta:** costruzione in AISI 316L - certificati EN 10204/2.2 - spessori diversi dallo standard.

Dimensioni

Ø	H mm	Tolleranze mm
21.3	-	-
26.9	-	-
33.7	14	0.030
42.4	14	0.039
48.3	14	0.048
60.3	21	0.083
76.1	23	0.123
88.9	25	0.163

Ø	H mm	Tolleranze mm
114.3	30	0.261
139.7	30	0.361
168.3	45	0.571
219.1	60	0.978
273	65	1.434
323.9	65	1.899
355.6	80	2.383



#### Cartella inox

**Esecuzione:** inox 304 con estremità lisce - spessore 2 mm.


**A richiesta:** costruzione in AISI 316L - certificati EN 10204/2.2 - spessori diversi dallo standard.

**N.B.:** Montaggio in accoppiamento a flange libere alluminio PN 10

Dimensioni

Ø	d <sub>1</sub>	d <sub>2</sub>	h	s
21.3	21.3	45	6	2
26.9	26.9	58	6	2
33.7	33.7	68	8	2
42.4	42.4	78	10	2
48.3	48.3	88	10	2
60.3	60.3	102	12	2
76.1	76.1	122	12	2
88.9	88.9	139	12	2

Ø	d <sub>1</sub>	d <sub>2</sub>	h	s
114.3	114.3	158	14	2
139.7	139.7	188	14	2
168.3	168.3	212	16	2
219.1	219.1	270	18	2
273	273	320	20	2
323.9	323.9	370	20	2
355.6	355.6	430	25	2
406.4	406.4	482	25	2



**FORINA S.r.l.**

Via Polveriera, 42

80141 – NAPOLI

P.IVA 04448850638

Tel. +39 081 7516077 pbx

Fax +39 081 7805490

[www.forina.it](http://www.forina.it)

